

# EUROBATEX® OC

<b>TYPE OF MATERIAL:</b>	Granulated Flexible Elastomeric Foam (FEF) held together by a polyurethane resin binder
<b>PRODUCT RANGE:</b>	Sheets available in a range of thicknesses from 10 mm to 40 mm. Available at density of 160 kg/m <sup>3</sup> or 240 kg/m <sup>3</sup> (tolerance -20 +120 kg/m <sup>3</sup> ). Different thicknesses are available upon request
<b>FIELDS OF APPLICATION:</b>	Acoustic absorption
<b>STORAGE CONDITIONS/SHELF LIFE:</b>	Store the material in a dry and clean environment at a temperature between 0 °C and 35 °C and a RH between 50% and 70%. Do not expose the material to heat or direct sunlight when stored

PHYSICAL PROPERTIES	RESULT OBTAINED		TEST METHOD
<b>OPERATING TEMPERATURE RANGE</b>	-45 °C +110 °C		-
<b>ACOUSTIC ABSORPTION (α)</b> Thk. 25 mm, Δ 240 Kg/m <sup>3</sup>	250 Hz 500 Hz 1000 Hz 2000 Hz 4000 Hz 5000 Hz	0,26 0,7 0,9 0,85 0,85 0,85	UNI EN ISO 354
<b>FIRE PERFORMANCE</b>	Self-extinguishing, does not spread flame		

All the normatives quoted in this document are updated to the latest issued version.  
 Union Foam S.p.A. reserves the right to modify any information at any time without prior notice.